

Amendments to the Claims:

Please amend the claims as shown in the following listing of claims:

1. **(currently amended)** A plastic glazing panel installation comprising:

a first glazing panel;

a ~~generally rectangular~~ second glazing panel of transparent plastic ~~having top, bottom and side edges;~~

a retainer frame;

a seal assembly secured to the retainer frame and ~~including sections of a perimeter channel forming a corresponding generally rectangular glazing opening for~~ forming a first perimeter channel receiving said first glazing panel therein and a second perimeter channel parallel to and spaced-apart from the first perimeter channel and receiving the edges of said second glazing panel therein;

wherein ~~said sections of said~~ second perimeter channel ~~each have a lip that together define~~ is formed by an inner wall and an outer lip spaced-apart from said inner wall;

wherein ~~said outer lip~~ forms an opening of smaller size than ~~said glazing opening and~~ said second glazing panel, so as to retain said second glazing panel in said second perimeter channel;

wherein said ~~retainer frame, said sections, and said glazing panel are sized and shaped~~ second perimeter channel is wider than a thickness of said second glazing panel, said outer lip is shorter than said inner wall, and said second glazing panel is sufficiently thin and flexible so that said second glazing panel is able to be easily bowed so as to allow opposite edges of said second glazing panel to be drawn together sufficiently to be able to be passed by the lips outer lip of opposite sections of said second perimeter channel and allow another edge of said second glazing panel to be received in a receiving channel section ~~extending along said glazing opening of said second perimeter channel~~ while said seal assembly is secured to said retainer frame; and

wherein said receiving channel section of said second perimeter channel is deeper than an opposite channel section of said second perimeter channel so that upon insertion of said another edge of said second glazing panel and movement towards the bottom of said receiving channel section of said second perimeter channel, an edge of said second glazing panel

opposite said another edge clears said lip of said opposite channel section of said second perimeter channel which is shallower than said receiving channel section of said second perimeter channel to enable insertion and removal of said second glazing panel into and out of ~~said glazing opening~~ said second perimeter channel through said opening while said seal assembly remains secured to said retainer frame; ~~and~~

~~wherein said perimeter channel and said lip are each located entirely outside the retainer frame.~~

2. **(currently amended)** The installation according to claim 1 wherein said receiving channel section has a resiliently compressible element disposed therein allowing sufficient movement upon pushing of another edge of said second glazing panel thereagainst so that said glazing panel edge opposite said another glazing panel edge clears the lip of said opposite channel section allowing removal of said second glazing panel, but thereafter upon release causes said second glazing panel to be repositioned to locate said another edge of said second glazing panel at an intermediate depth in said receiving channel section.

3. **(original)** The installation according to claim 2 wherein said compressible element comprises a bowed leaf spring disposed in the bottom of said receiving channel section so as to be compressible by said glazing panel another edge.

4. **(withdrawn)** The installation according to claim 2 wherein said compressible element comprises an elastomeric piece.

5. **(withdrawn)** The installation according to claim 4 wherein said elastomeric piece comprises a piece of elastomeric foam.

6. **(withdrawn)** The installation according to claim 4 wherein said elastomeric piece is formed with an opening in a lower portion allowing compression thereof.

7. **(currently amended)** The installation according to claim 1 wherein said receiving channel section is at the bottom of said ~~glazing opening~~ second perimeter channel, and further

including a positioner element selectively manipulatable to allow lowering of said second glazing panel and thereafter hold said glazing panel another edge at an intermediate position in said receiving channel section so that said opposite edge of said second glazing panel does not clear said lip of said channel section opposite said receiving channel section.

8. **(currently amended)** The installation according to claim 7 wherein said positioner element comprises a compressible element able to be compressed by pushing said glazing panel another edge thereagainst, and thereafter when said second glazing panel is released moving said opposite edge of said second glazing panel into said ~~one~~ channel section opposite said receiving channel section.

9. **(withdrawn)** The installation according to claim 7 wherein said positioner element comprises a plug in a lip of said bottom channel section, said plug having a stem portion protruding into said bottom channel section normally holding said glazing panel another edge at an elevated position therein but removable to allow lowering of said glazing panel another edge into said bottom channel section.

10. **(currently amended)** The installation according to claim 1 ~~further including a primary wherein said first~~ glazing panel ~~installed is~~ in said frame adjacent said second glazing panel and aligned therewith but spaced to one side, said second glazing panel being thinner ~~than said first glazing panel~~ and made of plastic to comprise a sacrificial glazing panel.

11. **(currently amended)** The installation according to claim 1 further including positioner means for allowing manipulating movement of said another edge of said second glazing panel into said receiving channel section to a sufficient extent to allow said opposite edge of said second glazing panel to clear said lip of said opposite channel section but after release of said second glazing panel to thereafter position said another edge of said second glazing panel at an intermediate position in said deeper receiving section of said perimeter channel to cause said opposite edge of said second glazing panel to be retained by said lip of said opposite channel section.

12. **(original)** The installation according to claim 11 wherein said positioner means is selected from the group consisting of a compressible leaf spring, a piece of compressible foam, an elastomeric element having an opening allowing ready compression thereof, or a slider-spring combination.

13. **(cancelled)**

14. **(cancelled)**

15. **(currently amended)** The installation according to claim 1 wherein said receiving channel section is at a top of said glazing opening second perimeter channel, and ~~the~~ a bottom edge of said second glazing panel rests on a bottom of the opposite channel section.

16. **(currently amended)** The installation according to claim 1 wherein said second glazing panel is sufficiently thin and flexible to enable insertion and removal of said second glazing panel into and out of said second perimeter channel sections without deforming said ~~retainer frame at the channel sections~~ said second perimeter channel.

17. **(currently amended)** The installation according to claim 1 wherein said lip forming said opposite channel section is angled so that said opposite channel section is wider at the lip opening than at the ~~glazing opening~~ bottom of the second perimeter channel.